

Approved body No. 1121

## Certificate of Constancy of Performance 1121-CPR-UK-AD7592

In compliance with Construction Products Regulation 2011 (retained EU law EUR 2011/305) as amended by the Construction Products (Amendment etc.) (EU Exit) Regulations 2019 and the Construction Products (Amendment etc.) (EU Exit) Regulations 2020, this certificate applies to the Construction Product:

## LCN 2016 Overhead door closer

Intended use: For use on fire rated single leaf and double leaf doors TRANSOM MOUNT CONCEALED APPLICATION

Essential characteristics	Performance	Designated Standard
	Mechanical Test Ref's: 65 PCT	
Fire Test Ref's: WF 142058 Issue 5 / WF 137145 & WF 137635		
Self closing 5.2.1 General		EN1154:1996/A1:2002/AC:2006
5.2.2 Durability	500,000 test cycles	
5.2.3 Closing moment	Pass size 4	
5.2.4 Opening moment	Pass size 4	
5.2.5 Efficiency	>60% size 4	
5.2.6 Closing time	Pass	
5.2.7 Angles of operation	Grade 4, 180°	
5.2.8 Overload performance	Pass	
5.2.9 Temperature dependence	-15°C to +40°C	
5.2.10 Fluid leakage	Pass	
5.2.11 Damage	Pass	
5.2.12 Latch control	Pass	
5.2.13 Back check (optional)	Pass	
5.2.14 Delayed closing	NPD	
(optional)		
5.2.15 Adjustable closing force	NPD	
(optional)		
5.2.16 Zero position (double	NPD	
action door closers only) 5.2.18 Fire/smoke door	Dana	
	Pass	
suitability Essential characteristics	Performance	Designated Standard
LSSCIIIIAI CIIAI ACIEI ISIICS	renomance	Designated Standard
Durability of Self Closing		EN1154:1996/A1:2002/AC:2006
5.2.2 Durability	500,000 test cycles	
5.2.17.1 corrosion	Grade 3 (96 hours)	
5.2.17.2 corrosion	Pass	
Dangerous Substances Annex ZA3	Pass: the materials in the door closer do not contain or release any dangerous substances in excess of the maximum levels specified in existing European material standards or any national	
	regulations	

EWC-QU-FT-480 (Issue 7) Page 1 of 2



Approved body No. 1121

## Certificate of Constancy of Performance 1121-CPR-UK-AD7592

Placed on the market under the name of

Allegion (UK) Ltd 35 Rocky Lane Aston Birmingham West Midlands B6 5RQ United Kingdom

and produced in the manufacturing plant

## B/006

This is coded format and the information is held by the Approved Body

This certificate attests that all provisions concerning the assessment and verification of constancy of performance and the performances described in Annex ZA of the standard(s)

EN 1154:1996/A1:2002/AC:2006

Under System 1 for the performance set out in this certificate are applied and that the Factory Production Control conducted by the manufacturer is assessed to ensure the constancy of performance of the construction product.

This certificate was first issued on **15/07/2021** and re-issued on **13/03/2023** will remain valid as long as neither the designated standard, the Construction Product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, or unless suspended or withdrawn by the Approved Product Certification Body.

UKCA certificate valid to: 12/03/2026



0087

Paul Duggan Certification Manager

Warringtonfire Testing and Certification Limited Suite 302, The Genesis Centre, Birchwood, Warrington, WA3 7BH, UK

EWC-QU-FT-480 (Issue 7)