

## Briton

### 4700 Series

#### Flush bolts

A range of manually operated flush bolts for use on equal or unequal pairs of doors to keep the inactive leaf locked.



Description:	Flush bolts - open type	
Ref:	Size	End Type
<b>4735.R.20.202</b>	202mm x 20mm	Radiused
<b>4735.R.20.300</b>	300mm x 20mm	Radiused
<b>4735.R.20.450</b>	450mm x 20mm	Radiused
<b>4735.R.20.600</b>	600mm x 20mm	Radiused
<b>4735.R.20.914</b>	914mm x 20mm	Radiused
<b>4735.S.20.202</b>	202mm x 20mm	Square
<b>4735.S.20.300</b>	300mm x 20mm	Square
<b>4735.S.20.450</b>	450mm x 20mm	Square
<b>4735.S.20.600</b>	600mm x 20mm	Square
<b>4735.S.20.914</b>	914mm x 20mm	Square



Description:	Flush bolts - Fully enclosed	
Ref:	Size	End Type
<b>4739.R.18.225</b>	225mm x 18mm	Radiused
<b>4739.S.18.225</b>	225mm x 18mm	Square

#### Certification

- Tested to EN 12051:1999
- Graded 4 3 - 0 1 3 1
- DoP available at [www.britoninspec.co.uk](http://www.britoninspec.co.uk)

#### Features & Functions

- Stainless steel Grade 304
- Available in a range of lengths up to 914mm for use on tall doors
- Square or radiused end versions
- Stainless steel lever action bolt
- Fully enclosed option particularly suitable for timber doors
- Supplied with stainless steel fixings
- Optional floor sockets available (see below)



Ref:	Description
<b>4736</b>	Plunger type dust excluding floor socket for use with flush bolts - concealed fixing
<b>4737</b>	Easy clean floor socket for use with flush bolts - face fixing.



**Allegion (UK) Limited**  
35 Rocky Lane, Aston, Birmingham B6 5RQ

Tel: +44 (0) 121 380 2400  
Email: [inspec@allegion.com](mailto:inspec@allegion.com)