

Ironmongery Schedule



Prepared for: ABC Architects
Project Title: Leisure Vertical Market
Our Ref: ABC123



Ironmongery Performance Specifications



1.0 Door Hardware

Briton Levers, Escutcheon's & Bathroom Indicators

Levers, escutcheon's and bathroom Indicators are supplied with bolt through fixings with Torx head to ensure a highly durable and tamperproof installation. Spindle is fixed by means of a grubscrew piercing a specially manufactured spindle which ensures maximum fixing strength.

Products have been tested to EN 1906 Grade 4 for performance characteristics (the highest in the standard for high frequency and violent use e.g. football stadiums). Tested to EN 1634 for fire rating (90 minutes timber & 4hours steel) and EN 179 for emergency exit applications in conjunction with Briton escape locks. Many products also meet the requirements of BS 8300 for inclusive access. Products will suit doors from 44mm to 54mm thickness.



Briton Pushplates

Pushplates are manufactured from 1.2mm stainless steel and are supplied as standard with radius corners and drilled and countersunk holes to suit face fixing. Screws are included. Grade 304 is standard but other grades are available.

Briton Signs

Signs are produced from 76mm diameter x 1.5mm stainless steel. Drilled and countersunk to suit face fixing. Screws are included.

Briton Flush Bolts

Tested to meet EN12051: 1999 Grade 4. Manufactured from stainless steel and available with square or radiused ends in a variety of lengths.



2.1 Overhead Door Controls

Door closers have been tested in accordance with EN 1154 for durability and performance and fire tested to EN 1634. Covered by the Allegion 10 year mechanical guarantee.

Briton 2700

Cast Iron body for high level of durability and long life performance. Cam action technology allows reliable closer power setting yet still be easy to open. All models feature backcheck and delayed action as standard. Variable closing power 2 to 5. CE classification 4 8 2-5 1 1 3 for all applications except push side transom which is 2-4. Fire door rating 2hr timber/1hr steel.



Tested to EN 1154 for mechanical performance & EN 1155 for electronically controlled devices



2.2 Electromagnetic Closers

Electromagnetic closers have been tested to EN 1154 for mechanical performance, EN 1155 for electronically controlled devices and EN 1634 for fire performance. Linked to fire alarm system, units will release under a fire alarm actuation and are fail-safe in the event of a loss of power. Devices are covered by the Allegion 10 year mechanical and 2 year electrical guarantee.

Briton 2720BD.TE

Cast iron body for high level of durability and long life performance. Cam action technology allows reliable closer power setting yet still be easy to open. Variable closing power 3 to 5.CE classification 3 8 3-5 11 3. Fire door rating 2hr timber/1hr steel. 24v electro-magnetic hold open track.

Briton 2130B.TE

Cast Iron body for rugged durability.3 cover options to offer a versatile architectural solution. CE classification 3 8 3-4 11 3. Fire door rating 2hr timber/4hr steel (dependant on cover option). 24v electro-magnetic hold open track.

Briton 1130B.TE

Cast aluminium body to offer a cost effective product. CE classification 3 8 3-4 11 3. Fire door rating 2hr timber/4hr steel* (dependant on cover option). 24v electro-magnetic hold open track.

Briton 996

Pressure die cast aluminium body for rugged durability. Hold open or free swing applications selectable at installation. CE certification (product reference 9963) 3 8 3 11 3, (product reference 9964) 3 8 4 11 3, & (product reference 9965) 3 8 5 11 3 Fire door rating 2hr timber.

3.0 Cylinder Lockcases

Lockcases have been tested in accordance with EN 12209 for durability and performance, EN 1634 for fire rating and where relevant EN 179 for emergency exits. Designed to be compatible with euro profile cylinders and bolt through furniture fixings for enhanced durability and performance. Supplied with stainless steel Grade 316 forends.



Tested to EN 1154 for mechanical performance & EN 1155 for electronically controlled devices



2.2 Electromagnetic Closers

Electromagnetic closers have been tested to EN 1154 for mechanical performance, EN 1155 for electronically controlled devices and EN 1634 for fire performance. Linked to fire alarm system, units will release under a fire alarm actuation and are fail-safe in the event of a loss of power. Devices are covered by the Allegion 10 year mechanical and 2 year electrical guarantee.

Briton 2720BD.TE

Cast iron body for high level of durability and long life performance. Cam action technology allows reliable closer power setting yet still be easy to open. Variable closing power 3 to 5.CE classification 3 8 3-5 11 3. Fire door rating 2hr timber/1hr steel. 24v electro-magnetic hold open track.

Briton 2130B.TE

Cast Iron body for rugged durability.3 cover options to offer a versatile architectural solution. CE classification 3 8 3-4 11 3. Fire door rating 2hr timber/4hr steel (dependant on cover option). 24v electro-magnetic hold open track.

Briton 1130B.TE

Cast aluminium body to offer a cost effective product. CE classification 3 8 3-4 11 3. Fire door rating 2hr timber/4hr steel* (dependant on cover option). 24v electro-magnetic hold open track.

Briton 996

Pressure die cast aluminium body for rugged durability. Hold open or free swing applications selectable at installation. CE certification (product reference 9963) 3 8 3 11 3, (product reference 9964) 3 8 4 11 3, & (product reference 9965) 3 8 5 11 3 Fire door rating 2hr timber.

3.0 Cylinder Lockcases

Lockcases have been tested in accordance with EN 12209 for durability and performance, EN 1634 for fire rating and where relevant EN 179 for emergency exits. Designed to be compatible with euro profile cylinders and bolt through furniture fixings for enhanced durability and performance. Supplied with stainless steel Grade 316 forends.



Ironmongery Performance Specifications



Briton 5400 Series

Grade 304 stainless steel single piece forend. All models CE classification 3 X 8 1 for use, durability, door mass and suitability for fire door. 90 mins timber & 4hr steel. 25° follower action with springing suitable for high frequency applications and double turn throw operation for 20mm deadbolt throw.

Briton 5500 Series

Grade 316 stainless steel single piece forend. All models CE classification 3 X 8 1 for use, durability, door mass and suitability for fire door, 90 mins timber & 4hr steel.

30° follower action with springing suitable for high frequency applications and single turn throw operation for 22mm deadbolt throw.

Briton 5600 Series

Grade 304 stainless steel single piece forend. All models CE classification 3 X 8 1 for use, durability, door mass and suitability for fire door. 90 mins timber & 4hr steel. 30° follower action with springing suitable for high frequency applications and single turn throw operation for 20mm bolt throw.



4.0 Cylinders

Cylinders are tested in accordance with EN 1303:2005. Cylinders include push resistance cams, anti-pick and anti-drill pins as standard.

Briton 75-29

6 pins plus check pin tumbler system. Serrated key. Patent protection to 2029. EN 1303 classification 1 6 0 0 0 C 5 2

CISA Tekno

10 pin tumbler system. Patent protection to 2026. Non-serrated flat-key. EN 1303 classification 1 6 0 1 0 C 6 0

CISA Astral

10 pin tumbler system. Non-serrated flat-key. EN 1303 classification 1 6 0 1 0 C 6 0

CISA Astral S

10 pin tumbler system. Non-serrated flat-key. EN 1303 classification 1 6 0 1 0 C 6 2



Ironmongery Performance Specifications

Patented **Fast-Fix** cable system reduces installation time by up to 50%



5.0 Exit Hardware

Panic hardware to EN 1125 and emergency hardware to EN179. All panic hardware has been tested to EN 1634, 2 hours timber & steel. All products supplied standard with Pullman latches for quieter operation.

Briton 560 & 570

Designed with patented Fast-Fix cable system reduces installation by up to 50%. Cycle tested to 200,000 cycles. CE classification (product reference 570) 3 77 B 1 4 2 2 B A, (product reference 560) 3 77 B 1 4 2 2 A A.

Briton 581

Single push pad for emergency exit application where prior knowledge operation is required. CE certification 3 77 B 1 4 5 2 B A

Von Duprin 98 & 99

Robust construction tested to EN 1125 and ANSI A156.3.

Tested to 500,000 cycles. CE certification 3 7 6 B 1 3 2 2 B A

6.0 Hinges

Tested in accordance with EN 1935:2002 with the CE classification 476114013 (Grade 13). All are template drilled to ensure accuracy.



Hardware Schedule

Re: Leisure

Ironmongery & Security Hardware Schedule

Hardware Set Ref: LE Single Action Lockable Fire Door

| Product | Description | Quantity | Unit |
|--------------------|--|----------|------|
| 0247 32 | Normbau 52mm Euro Profile Cylinder Escutcheons | 1 | Pair |
| 0516 01 | Normbau 20mm Dia Steel Cored Nylon Levers on Rose | 1 | Pair |
| 0842 01 | Normbau Floor Mounted Door Stop | 1 | Each |
| 7000 42 | Normbau Nylon Kickplate Size to order | 2 | Each |
| 4801.316.SS | Briton Briton Stainless Steel Hinges - 316 | 3 | Each |
| 2321B.T.S.SSS | Briton Door Closer Adj Size 2-4 with B/C & Softline Cover - Door Push Side | 1 | Each |
| 5660.60.R.SS | Briton Escape latch - Euro Profile 60mm Backset 72mm Centres Radius Forend- with Split follower | 1 | Each |
| M.75-29.EK3535T.NP | Briton Master Keyed 75-29 Euro Cylinder & Turn 35/35 NP finish (Differ keys supplied separately) | 1 | Each |
| 4750.10.SS | Briton Fire Door Keep Shut Symbol, 76mm Dia x 1.5mm, C/W SSS Pozi Drive Screws, SS304 | 2 | Each |

Hardware Schedule

Re: Leisure

Ironmongery & Security Hardware Schedule

Hardware Set Ref: LE1 Single Unlatched Fire Door

| Product | Description | Quantity | Unit |
|----------------|---|----------|------|
| 0363 19 | Normbau Nylon Pull Handle 34mm Dia x 400mm Centres | 1 | Each |
| 0365 12 | Normbau Pull Handle Fixing Pack | 1 | Each |
| 0842 01 | Normbau Floor Mounted Door Stop | 1 | Each |
| 7000 15 | Normbau Nylon Push Plate Radius Corners 500 x 100mm | 1 | Each |
| 7000 42 | Normbau Nylon Kickplate Size to order | 2 | Each |
| 4801.316.SS | Briton Briton Stainless Steel Hinges - 316 | 3 | Each |
| 2720BD.T.A.SSS | Briton Door Closer Adj Size 2-5 with B/C & D/A - Door Pull Side | 1 | Each |
| 4750.10.SS | Briton Fire Door Keep Shut Symbol, 76mm Dia x 1.5mm, C/W SSS Pozi Drive Screws, SS304 | 2 | Each |

Hardware Schedule

Re: Leisure

Ironmongery & Security Hardware Schedule

Hardware Set Ref: LE10 Double Unlatched Fire Door

| Product | Description | Quantity | Unit |
|----------------|---|----------|------|
| 0363 19 | Normbau Nylon Pull Handle 34mm Dia x 400mm Centres | 2 | Each |
| 0365 12 | Normbau Pull Handle Fixing Pack | 2 | Each |
| 0842 01 | Normbau Floor Mounted Door Stop | 2 | Each |
| 7000 15 | Normbau Nylon Push Plate Radius Corners 500 x 100mm | 2 | Each |
| 7000 42 | Normbau Nylon Kickplate Size to order | 2 | Each |
| 4801.316.SS | Briton Briton Stainless Steel Hinges - 316 | 6 | Each |
| 2720BD.T.A.SSS | Briton Door Closer Adj Size 2-5 with B/C & D/A - Door Pull Side | 2 | Each |
| 4750.10.SS | Briton Fire Door Keep Shut Symbol, 76mm Dia x 1.5mm, C/W SSS Pozi Drive Screws, SS304 | 4 | Each |

Hardware Schedule

Re: Leisure

Ironmongery & Security Hardware Schedule

Hardware Set Ref: LE11 Single latched Fire Door

| Product | Description | Quantity | Unit |
|----------------|---|----------|------|
| 0516 01 | Normbau 20mm Dia Steel Cored Nylon Levers on Rose | 1 | Pair |
| 0842 01 | Normbau Floor Mounted Door Stop | 1 | Each |
| 7000 42 | Normbau Nylon Kickplate Size to order | 2 | Each |
| 4801.316.SS | Briton Briton Stainless Steel Hinges - 316 | 3 | Each |
| 2720BD.T.A.SSS | Briton Door Closer Adj Size 2-5 with B/C & D/A - Door Pull Side | 1 | Each |
| 5540.60.S.SS | Briton Latch - 60mm Backset Square Forend | 1 | Each |
| 4750.10.SS | Briton Fire Door Keep Shut Symbol, 76mm Dia x 1.5mm, C/W SSS Pozi Drive Screws, SS304 | 2 | Each |

Hardware Schedule

Re: Leisure

Ironmongery & Security Hardware Schedule

Hardware Set Ref: **LE2** **Single latched Fire Door Electro Mag Hold Open**

| Product | Description | Quantity | Unit |
|-----------------|---|----------|------|
| 0516 01 | Normbau 20mm Dia Steel Cored Nylon Levers on Rose | 1 | Pair |
| 0842 01 | Normbau Floor Mounted Door Stop | 1 | Each |
| 7000 42 | Normbau Nylon Kickplate Size to order | 2 | Each |
| 4801.316.SS | Briton Briton Stainless Steel Hinges - 316 | 3 | Each |
| 2720BD.TE.A.SSS | Briton Door Closer Adj Size 2-5 with B/C, D/A & Electro HO - Door Pull Side | 1 | Each |
| 5540.60.S.SS | Briton Latch - 60mm Backset Square Forend | 1 | Each |
| 4726.SS | Briton Pull Handle Universal Fixing Pack - Bolt Through (Timber), Face Fix (Timber), B2B (Timber and Glass Fixing Kit 8-12mm) | 1 | Each |
| 4750.12.SS | Briton Automatic Fire Door Keep Clear Symbol, 76mm Dia x 1.5mm, C/W SSS Pozi Drive Screws, SS304 | 2 | Each |

Hardware Schedule

Re: Leisure

Ironmongery & Security Hardware Schedule

Hardware Set Ref: **LE3** **Double Unlatched Fire Door Electro Mag Hold Open**

| Product | Description | Quantity | Unit |
|-----------------|--|----------|------|
| 0363 19 | Normbau Nylon Pull Handle 34mm Dia x 400mm Centres | 2 | Each |
| 0365 12 | Normbau Pull Handle Fixing Pack | 2 | Each |
| 0842 01 | Normbau Floor Mounted Door Stop | 2 | Each |
| 7000 15 | Normbau Nylon Push Plate Radius Corners 500 x 100mm | 2 | Each |
| 7000 42 | Normbau Nylon Kickplate Size to order | 4 | Each |
| 4801.316.SS | Briton Briton Stainless Steel Hinges - 316 | 6 | Each |
| 2720BD.TE.A.SSS | Briton Door Closer Adj Size 2-5 with B/C, D/A & Electro HO - Door Pull Side | 2 | Each |
| 4750.12.SS | Briton Automatic Fire Door Keep Clear Symbol, 76mm Dia x 1.5mm, C/W SSS Pozi Drive Screws, SS304 | 4 | Each |

Hardware Schedule

Re: Leisure

Ironmongery & Security Hardware Schedule

Hardware Set Ref: **LE4** **Double latched Fire Door**

| Product | Description | Quantity | Unit |
|-----------------|---|----------|------|
| 0516 01 | Normbau 20mm Dia Steel Cored Nylon Levers on Rose | 1 | Pair |
| 0842 01 | Normbau Floor Mounted Door Stop | 2 | Each |
| 4751.R.20.225 | Normbau Colour Coated Lever Action Flush Bolt 225x20mm | 2 | Each |
| 7000 42 | Normbau Nylon Kickplate Size to order | 4 | Each |
| 4801.316.SS | Briton Briton Stainless Steel Hinges - 316 | 6 | Each |
| 2720BD.TE.A.SSS | Briton Door Closer Adj Size 2-5 with B/C, D/A & Electro HO - Door Pull Side | 2 | Each |
| 5540.60.S.SS | Briton Latch - 60mm Backset Square Forend | 1 | Each |
| 4726.SS | Briton Pull Handle Universal Fixing Pack - Bolt Through (Timber), Face Fix (Timber), B2B (Timber and Glass Fixing Kit 8-12mm) | 2 | Each |
| 4736.SS | Briton Dust Excluding Socket - Concealed | 1 | Each |
| 4750.10.SS | Briton Fire Door Keep Shut Symbol, 76mm Dia x 1.5mm, C/W SSS Pozi Drive Screws, SS304 | 4 | Each |

Hardware Schedule

Re: Leisure

Ironmongery & Security Hardware Schedule

Hardware Set Ref: LE5 Toilet Door M or F

| Product | Description | Quantity | Unit |
|----------------|--|----------|------|
| 0358 34 | Normbau Nylon Bathroom Indicator & Turn | 1 | Each |
| 0510 01 | Normbau Nylon Male Bathroom Symbol 130mm height | 1 | Each |
| 0510 02 | Normbau Nylon Female Bathroom Symbol 130mm height | 1 | Each |
| 0516 01 | Normbau 20mm Dia Steel Cored Nylon Levers on Rose | 1 | Pair |
| 0842 01 | Normbau Floor Mounted Door Stop | 1 | Each |
| 7000 42 | Normbau Nylon Kickplate Size to order | 2 | Each |
| 4801.316.SS | Briton Briton Stainless Steel Hinges - 316 | 3 | Each |
| 2720BD.T.A.SSS | Briton Door Closer Adj Size 2-5 with B/C & D/A - Door Pull Side | 1 | Each |
| 5530.60.S.SS | Briton Bathroom - 60mm Backset 8mm Spindle 78mm Square Forend | 1 | Each |
| 4760.304.SS | Kickplate 1.2mm satin stainless steel grade 304 - price per square metre | 2 | Each |

Hardware Schedule

Re: Leisure

Ironmongery & Security Hardware Schedule

Hardware Set Ref: LE6 Single Panic Exit Door

| Product | Description | Quantity | Unit |
|-------------|---|----------|------|
| 7000.42 | Normbau Nylon Kickplate Size to order | 1 | Each |
| 4801.316.SS | Briton Briton Stainless Steel Hinges - 316 | 3 | Each |
| 1413E/LE.SE | Briton Outside Access Device - Lever Operated c/w Euro-Profile Cylinder | 1 | Each |
| 561.SE | Briton Push Bar - 1 Point Locking Panic Device | 1 | Each |
| 574.V.BM | Briton Upper & lower pullman kit black | 1 | Each |
| 574.V.SE | Briton Upper & lower pullman kit silver | 1 | Each |

Hardware Schedule

Re: Leisure

Ironmongery & Security Hardware Schedule

Hardware Set Ref: LE7 Single Panic Exit Door c/w Digital Lock

| Product | Description | Quantity | Unit |
|-------------|---|----------|------|
| 7000.42 | Normbau Nylon Kickplate Size to order | 1 | Each |
| 4801.316.SS | Briton Briton Stainless Steel Hinges - 316 | 3 | Each |
| 561.SE | Briton Push Bar - 1 Point Locking Panic Device | 1 | Each |
| 574.V.BM | Briton Upper & lower pullman kit black | 1 | Each |
| 9260.PVD-BS | Briton Panic Hardware Push Button Mechanical Digital Lock with Lever Handle (PVD-BS Finish) | 1 | Each |

Hardware Schedule

Re: Leisure

Ironmongery & Security Hardware Schedule

Hardware Set Ref: LE8 Double Panic Exit Door (Rebated)

| Product | Description | Quantity | Unit |
|-------------|---|----------|------|
| 7000 42 | Normbau Nylon Kickplate Size to order | 2 | Each |
| 4801.316.SS | Briton Briton Stainless Steel Hinges - 316 | 6 | Each |
| 1413E/LE.SE | Briton Outside Access Device - Lever Operated c/w Euro-Profile Cylinder | 1 | Each |
| 561.SE | Briton Push Bar - 1 Point Locking Panic Device | 2 | Each |
| 574.V.SE | Briton Upper & lower pullman kit silver | 1 | Each |

Hardware Schedule

Re: Leisure

Ironmongery & Security Hardware Schedule

Hardware Set Ref: LE9 Double Panic Exit Door (Non Rebated)

| Product | Description | Quantity | Unit |
|-------------|---|----------|------|
| 4801.316.SS | Briton Briton Stainless Steel Hinges - 316 | 6 | Each |
| 1413E/LE.SE | Briton Outside Access Device - Lever Operated c/w Euro-Profile Cylinder | 1 | Each |
| 561.SE | Briton Push Bar - 1 Point Locking Panic Device | 2 | Each |
| 574.V.SE | Briton Upper & lower pullman kit silver | 2 | Each |