

# CONSTRUCTION PRODUCTS REGULATION 2011 DECLARATION OF PERFORMANCE

# No. AL-0000402349

1. Unique identification code of the product-type:

## LCN 1461 Overhead Door Closer

2 Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR:

# LCN 1461 Overhead Door Closer

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

## For use on fire and smoke compartmentation doors (to fulfil the self-closing requirements of such doors).

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

### Allegion (UK) Limited 35 Rocky Lane Aston Birmingham B6 5RQ

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

# N/A

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:

### System 1

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

## EN 1154: 1996: A1: 2002/AC:2006 Notified Certification body No.2812 performed the type testing and issued test reports. Certificate of Constancy of Performance - 2812-CPR- AD0097

8. European Technical Assessment:

## N/A

9. Declared performance

Essential characteristics	Performance	Harmonised technical specification
<u>Self closing</u> 5.2.1 General		
Applications	Door Mount Pull Side (Fig 1) Parallel Arm Application (Fig 66)	
5.2.2 Durability		EN 1154: 1996: A1: 2002/AC:2006
5.2.3 Closing moment	500,000	
5.2.4 Opening moment	Pass size 2-5	
5.2.5 Efficiency	Pass size 2-5	



>50% size 2	
>65% size 5	
Pass	
Grade 4, 180°	
Pass	
-15°C to +40°C	
Pass	
Pass	
Pass	
Pass	
NPD	
Pass	
NPD	
Pass	
Performance	Harmonised technical specification
500,000	
-	
Pass	EN 1154: 1996: A1: 2002/AC:2006
Pass	
	>65% size 5 Pass Grade 4, 180° Pass -15°C to +40°C Pass Pass Pass Pass NPD Pass NPD Pass NPD Pass Source 500,000 Grade 3 (96 hours) Pass

10. The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Peter Hancox UK General Manager

Petettago

Allegion (UK) Limited 35 Rocky Lane Aston Birmingham B6 5RQ

27th May 2025



# **Declaration of performance**

### CONSTRUCTION PRODUCTS REGULATION 2011 DECLARATION OF PERFORMANCE

#### No. AL-0000402349

2. Unique identification code of the product-type:

#### LCN 1461 Overhead Door Closer

2 Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR:

# LCN 1461 Overhead Door Closer

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

For use on fire and smoke compartmentation doors (to fulfil the self-closing requirements of such doors).

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

# Allegion (UK) Limited 35 Rocky Lane Aston Birmingham B6 5RQ

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

#### N/A

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:

# System 1

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

### EN 1154: 1996: A1: 2002/AC:2006 Notified Certification body No.2812 performed the type testing and issued test reports. Certificate of Constancy of Performance - 2812-CPR- AD0097

8. European Technical Assessment:

N/A

9. Declared performance

Essential characteristics	Performance	Harmonised technical specification
<u>Self closing</u>		
5.2.1 General		
Applications	Transom Mount Push Side (Fig 61)	
	500.000	
5.2.2 Durability	500,000	EN 1154: 1996: A1: 2002/AC:2006
5.2.3 Closing moment	Pass size 2-5	



Pass size 2-5	
>50% size 2	
>65% size 5	
Pass	
Grade 4, 180°	
Pass	
-15°C to +40°C	
Pass	
Pass	
Pass	
NPD	
NPD	
Pass	
NPD	
Pass	
Performance	Harmonised technical specification
500.000	
•	
Pass	EN 1154: 1996: A1: 2002/AC:2006
Pass	
_	>65% size 5 Pass Grade 4, 180° Pass -15°C to +40°C Pass Pass Pass NPD Pass NPD Pass Performance 500,000 Grade 3 (96 hours) Pass

The performance of the product identified above is in conformity with the set of declared performance/s. This
declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of
the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Peter Hancox UK General Manager

Petettago

Allegion (UK) Limited 35 Rocky Lane Aston Birmingham B6 5RQ

24th April 2025