

## Declaration of Performance

### CONSTRUCTION PRODUCTS REGULATION 2011 DECLARATION OF PERFORMANCE

**No. AL-0000402358**

1. Unique identification code of the product-type:

**LCN 4023T Overhead Door Closer**

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR:

**LCN 4023T Overhead Door Closer**

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

**For use on fire and smoke compartmentation doors (to fulfil the self-closing requirements of such doors).**

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

**Allegion (UK) Limited  
35 Rocky Lane  
Aston  
Birmingham  
B6 5RQ**

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

**N/A**

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:

**System 1**

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

**EN 1154: 1996: A1: 2002/AC:2006  
Notified Certification body No.2812 performed the type testing and issued test reports.  
Certificate of Constancy of Performance - 2812-CPR- AD0073**

8. European Technical Assessment:

**N/A**

9. Declared performance

| Essential characteristics   | Performance  | Harmonised technical specification   |
|---|--|--|
| <b>Self closing</b><br><b>5.2.1 General</b><br><br><b>Application</b><br><br><b>5.2.2 Durability</b><br><b>5.2.3 Closing moment</b> | <br><br><br><b>Transom Mount Pull<br/>(Top Jamb)</b><br><br><br><b>500,000</b><br><b>Pass size 3</b> | <br><br><br><br><br><br><br><br><br><b>EN 1154: 1996: A1: 2002/AC:2006</b> |

|  |   |   |
|--|---|---|
| <b>5.2.4 Opening moment</b><br><b>5.2.5 Efficiency</b><br><br><b>5.2.6 Closing time</b><br><b>5.2.7 Angles of operation</b><br><b>5.2.8 Overload performance</b><br><b>5.2.9 Temperature dependence</b><br><b>5.2.10 Fluid leakage</b><br><b>5.2.11 Damage</b><br><b>5.2.12 Latch control</b><br><b>5.2.13 Backcheck</b><br><b>5.2.14 Delayed Action</b><br><b>5.2.15 Adjustable closing force</b><br><b>5.2.16 Zero position (double action doors only)</b><br><b>5.2.18 Fire / smoke doors</b> | <b>Pass size 3</b><br><b>&gt;55% size 3</b><br><br><b>Pass</b><br><b>Grade 3 (&gt;105° &lt;180°)</b><br><b>Pass</b><br><b>-15°C to +40°C</b><br><b>Pass</b><br><b>Pass</b><br><b>Pass</b><br><b>Pass</b><br><b>NPD</b><br><b>NPD</b><br><b>NPD</b><br><b>Pass</b> |   |
| <b>Essential characteristics</b>   | <b>Performance</b>  | <b>Harmonised technical specification</b> |
| <u><b>Durability of Self Closing</b></u><br><b>5.2.2 Durability</b><br><b>5.2.17.1 corrosion</b><br><b>5.2.17.2 corrosion</b><br><br><u><b>Dangerous Substances</b></u><br><u><b>Annex ZA3</b></u>   | <b>500,000</b><br><b>Grade 3 (96 hours)</b><br><b>Pass</b><br><br><b>Pass</b>   | <b>EN 1154: 1996: A1: 2002/AC:2006</b>    |

10. The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Peter Hancox  
UK General Manager



Allegion (UK) Limited  
35 Rocky Lane  
Aston  
Birmingham  
B6 5RQ

27th May 2025